

## TABLE MOUNTED BLINDSTITCH MACHINES

# MODEL 75T

ALL-PURPOSE • PORTABLE • SINGLE THREAD CHAINSTITCH, BLINDSTITCH MACHINE

SWING-DOWN CYLINDER ARM, METAL SWING PLATE  
ADJUSTABLE THREAD TENSION

1 to 1 NON-SKIP STITCH AND 2 to 1 SKIP STITCH

Plus... Stitch penetration and stitch length adjustment dials give you big-machine features in a light-weight, compact and fully portable unit

*Ideal for alteration rooms, tailors, clothing rentals, dry cleaners, department stores, dressmakers and home use*


Perfect for sewing all weights of materials including synthetics, woolens, cottons, fabrics and knits

1 to 1 non-skip stitches, typical operations include felling edge tapes, bottoms of trousers, cuffs, wiggling in sleeves, facings to canvas and knit goods, turned-up bottoms of fully lined coats, padding collars and lapels, and reinforcing trouser seats

2 to 1 skip stitch for hemming dresses, skirts, slacks, trousers, sportswear, ladies coats, draperies, blouses and other articles

Suitable for felling operations requiring a skipstitch to simulate hand-stitching

2 to 1 skip stitch is recommended for synthetics and other lightweight materials and 1 to 1 for heavier cotton, woolen and linen goods



Featuring  
SWING-DOWN  
CYLINDER ARM  
with  
METAL SWING PLATE



### SPECIFICATIONS

Speed, Max. (S.P.M.)	1000 *
Stitch Length, Max.	3 1/2 s.p.i. (7mm)
Needle Style	LWX 6T
Cylinder Diameter	1 5/8" (40 mm)
Work Space (Needle to Arm)	4" (100 mm)
Stitch Type	103

# MODEL 817


SINGLE THREAD CHAINSTITCH BLINDSTITCH MACHINE

- Skip and non-skip stitch lever
- Swing-down, narrow cylinder arm allows for easy insertion and removal of work
- Adjustable thread tension
- 1 to 1 non-skip stitch and 2 to 1 skip stitch
- Stitch depth penetration and stitch length adjustment dials
- Swing-away work plate for extended working space



### SPECIFICATIONS

Speed, Max. (S.P.M.)	2500 *
Stitch Length, Max.	2 1/2 s.p.i. (9mm)
Needle Style	300 LG
Looper	162
Cylinder Diameter	2 1/4" (57 mm)
Work Space (Needle to Arm)	7" (180 mm)
Stitch Type	103



Perfect for sewing all weights of materials including synthetics, woolens, cottons, fabrics and knits

1 to 1 non-skip stitches, typical operations include felling edge tapes, bottoms of trousers, cuffs, wiggling in sleeves, facings to canvas and knit goods, turned-up bottoms of fully lined coats, padding collars and lapels, and reinforcing trouser seats

2 to 1 skip stitch for hemming dresses, skirts, slacks, trousers, sportswear, ladies coats, draperies, blouses and other articles

Suitable for felling operations requiring a skipstitch to simulate hand-stitching

2 to 1 skip stitch is recommended for synthetics and other lightweight materials and 1 to 1 for heavier cotton, woolen and linen goods

# MODEL 1118-3

SINGLE THREAD CHAINSTITCH BLINDSTITCH MACHINE

- Skip and non-skip stitch lever
- Swing-down, narrow cylinder arm allows for easy insertion and removal of work piece
- Adjustable thread tension
- 1 to 1 non-skip stitch and 2 to 1 skip stitch
- Stitch length adjustment by push-button
- Stitch depth penetration adjustment dials
- Easy-open, swing-away work plate for extended working space



### SPECIFICATIONS

Speed, Max. (S.P.M.)	3000 *
Stitch Length, Max.	2 1/2 s.p.i. (3mm - 9mm)
Needle Style	300 LG
Cylinder Diameter	2 1/4" (57 mm)
Work Space (Needle to Arm)	7" (180 mm)
Stitch Type	103